

ES-7616-P16K

16 Ch & 16 POE Network Video Recorder




Features

- Up to 16-Ch IP cameras input
- 160Mbps Bit rate Input Max and 160Mbps Bit rate Output Max
- Third-party network cameras supported
- Up to 12MP resolution recording
- HDMI and VGA independent output
- HDMI 4K output
- 2 SATA HDD interface up to 8TB each



Physical Interfaces



Index	Description
1	AUDIO IN
2	AUDIO OUT
3	VGA Interface
4	HDMI Interface
5	Controller Port, Alarm In/Alarm Out
6	LAN Network Interface
7	USB 3.0 Interface.
8	GND
9	100 to 240 VAC power supply
10	Power Switch
11	Network Interfaces with PoE function

Model Number

ES-7616-P16K

Video Compression	H.265 / H.264+ / H.264 / MJPEG
IP Video Input	16 Ch. (160 Mbps Max input)
Video Output	1 HDMI, 1 VGA
Audio Input/Output	1/1
Two-way Audio	1/1
Real-time recording resolution	Up to 12 MP
HDMI Output Resolution	4K
VGA Output Resolution	1080P, 60Hz
Synchronous Playback	2 Ch. @ 4K, or 8 Ch. @ 1080p, 16 Ch. @ 720p
Network Interface	1 RJ45 10M/100M/1000M
PoE Network Interfaces/Built-in switch	16 independent 10/100 Mbps PoE network interfaces
Internal SATA	2 SATA interfaces (up to 8TB ea)
Alarm I/O	4/1
USB interface	1 x USB2.0, 1 x USB 3.0
Operation Temperature	-10 °C ~ +55 °C
Chassis	385mm chassis
Dimension	15.2"W x 12.4"D x 2.0"H
Power Supply	100 ~ 240VAC
Weight	6.6 lbs

NOTE

The ES-7616-P16K provide 16 network Interfaces with PoE function.