

ES-5483-SZ

8MP WDR Vari-focal Network Bullet Camera

EYESONIC™



Key Features

- 1/2.5" Progressive Scan CMOS
- 3840 x 2160 resolution
- H.265, H.265+
- P 120dB WDR
- IP67, IK10
- BLC/30 DNR/ROI
- Smart encoding: Support low bit rate, low latency
- 4 behavior analyses and face detection

Model Number

ES - 5483 - SZ

Image sensor	1/2.5" progressive scan CMOS
Min. illumination	0.01lux @ F1.2, AGC on, 0.014 lux @ F1.4, AGC on
Shutter time	1/3 ~ 1/100,000s
Day & Night	IR Cut Filter
Focal Length	2.8 - 12mm
Wide dynamic range	360°
Proportional range	Rotation speed can be adjusted automatically
Video output	1.0V[p-p]/75?, PAL or NTSC composite, BNC
Audio input	1 Audio output interface, Line input: 2~2.4V
Max. image resolution	3840x2160
Frame rate	25fps (1920x1080), 25fps (1280x720), 30fps (1920x1080), 30fps (1280x720)
Alarm trigger	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception, storage error
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
System compatibility	ONVIF, PSIA, CGI
General functionalities	Flickerless, dual stream, heartbeat, mirror, user authentication, video mask, watermark
Communication interface	1 RJ45 10M / 100M ethernet port
On-board storage	Built-in Micro SD card slot, up to 128 GB
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F)
Power supply	12 VAC, 1.5A, max. 17W; PoE (802.3at) 42.5V to 57V), 0.1A to 0.5A, max. 19W
Humidity	95% or less
Ingress protection level	IP67, IK10
Dimensions	5.67" x 13.10"
API	ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
Simultaneous Live View	Up to 6 channels
User/Host	Up to 32 users
Web Browser	IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+
Weight	4.17 lbs

www.eyesonic.com