

ES - PS7516GE

16 Port PoE Full Gigabit Managed Ethernet Switch



KEY FEATURES

The 16 ports PoE full Gigabit managed Ethernet switch(abbreviated to 16P switch), which provide 16* PoE Gigabit downlink Ethernet ports , 4* Gigabit uplink optical fiber ports. The Products support IEEE 802.3 af/at ,support Web layer-2 network management and PoE management.Products are widely used in security surveillance, network engineering projects and so on.

MODEL NUMBER

ES-PS7516GE

Power Supply(16p switch)	Mains on load
Voltage Range	AC 100~240V 50/60Hz Auto-sensing
Consumption	320W
Ethernet Port	Copper ports: 10/100/1000Mbps adaptive Rj45 ports support IEEE 802.3 af/a SFP ports:1000Base-X SFP port(Mini-GBIC)
Transmission Distance	Copper ports:100m SFP ports: depend on SFP module
PoE	Single port<30W,whole<270W
Network Standard	IEEE802.3 ,IEEE802.3u,IEEE802.3ab, IEEE802.3Z, IEEE802.3X, IEEE 802.1Q IEEE 802.1p IEEE 802.3ad , IEEE 802.1D, IEEE 802.1X
Switch Capacity	40Gbps
Packet Buffer	12Mb
Packet Forwarding Rate	30Mpps
MAC Address Management	16K
ESD	Management L2 + PoE 6KV/8KV Per:IEC61000-4-2
Lighting Protection	6KV Per: IEC61000-4-5
Working Temperature	-10°C~50°C
Storage Temperature	-40°C~85°C
Humidity(noncondensing)	0~95%
Dimension(LxWxH)	442mm×320mm×44mm
Material	Sheet Metal
Color	Black
Weight	4.35Kg