

# ES - PS7524GE

24 Port PoE Full Gigabit Managed Ethernet Switch



## KEY FEATURES

The 24 ports PoE full Gigabit managed Ethernet switch(abbreviated to 24P switch), which provide 24\* PoE Gigabit downlink Ethernet ports , 4\* Gigabit uplink optical fiber ports. The Products support IEEE 802.3 af/at ,support Web layer-2 network management and PoE management.Products are widely used in security surveillance, network engineering projects and so on.

## MODEL NUMBER

**ES-PS7524GE**

<b>Power Supply(24p switch)</b>	Mains on load
<b>Voltage Range</b>	AC 100~240V 50/60Hz Auto-sensing
<b>Consumption</b>	450W
<b>Ethernet Port</b>	Copper ports: 10/100/1000Mbps adaptive Rj45 ports support IEEE 802.3 af/a SFP ports:1000Base-X SFP port(Mini-GBIC)
<b>Transmission Distance</b>	Copper ports:100m SFP ports: depend on SFP module
<b>PoE</b>	Single port<30W,whole<390W
<b>Network Standard</b>	IEEE802.3 ,IEEE802.3u,IEEE802.3ab, IEEE802.3Z, IEEE802.3X, IEEE 802.1Q IEEE 802.1p IEEE 802.3ad , IEEE 802.1D, IEEE 802.1X
<b>Switch Capacity</b>	56Gbps
<b>Packet Buffer</b>	12Mb
<b>Packet Forwarding Rate</b>	41.66Mpps
<b>MAC Address Management</b>	16K
<b>ESD</b>	Management L2 + PoE 6KV/8KV Per:IEC61000-4-2
<b>Lighting Protection</b>	6KV Per: IEC61000-4-5
<b>Working Temperature</b>	-10°C~50°C
<b>Storage Temperature</b>	-40°C~85°C
<b>Humidity(noncondensing)</b>	0~95%
<b>Dimension(LxWxH)</b>	442mm×320mm×44mm
<b>Material</b>	Sheet Metal
<b>Color</b>	Black
<b>Weight</b>	4.35Kg