

HAC346-OD

5MP Exterior IR Dome Camera

EYESONIC™



- IVMS HD-TVI 5MP Exterior IR Dome Camera OSD menu,
- 3D DNR, 130 dB true WDR 5MP Video
- Output HD-TVI Technology OSD menu,
- DNR EXIR 2.0,
- Smart IR,
- up to 30 m IR distance IP67,
- IK10
- Up the Coax (control over coax)

HAC346-OD

Camera

Image Sensor	5MP CMOS
Resolution	2560(H)*1944(V)
Min. Illumination	0.003 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/30 s to 1/50,000 s
Lens	2.8 mm fixed lens
Angle Adjustment	Pan: 0° to 355°, Tilt: 0° to 75°, Rotate: 0° to 355°
Day & Night	IR Cut Filter
Video Frame Rate	TVI: 2MP@25fps, 2 MP@30fps, 4MP@25fps, 4MP@30fps, 5MP@20fps AHD: 4MP@25fps, 4MP@30fps, 5MP@20fps CVI: 4MP@25fps, 4MP@30fps CVBS: PAL, NTSC
AGC	Supported
Day/Night Mode	Auto/Color/Black and White
WDR	≥ 130 dB
Working Temperature	-40 °C to 60 °C (-40 °F to 140 °F),
Humidity	humidity: 90% or less (noncondensing)
Power Supply	12 VDC±25%
Power Consumption	Max. 5.8W
Weather Proof Ratings	IP67, IK10
IR Range	Up to 30 m
Communication	OSD (UTC Control) via DVR
Weight	Approx.500 g (1.10 lb.)
Dimensions	Φ 111 mm × 82.4 mm (Φ 4.4" × 3.2")
Electrical Box	HTH-280ZJ-DM18
Wall Mount	HTH-258ZJ, HTH-272ZJ-110B
Pendant	HTH-271ZJ-110
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ