

# ES-6986-F-H

8MP Panaromic Dome Camera

**EYESONIC™**



## Key Features

- High quality resolution: Up to 4096 x 1800
- Image Sensor: 1/1.8" Progressive Scan CMOS
- 8 MP Real-time Video
- Day & Night
- Audio 1/1 and Alarm 1/1
- Image stitching adjustment
- IP66 Outdoor

## Model Number

**ES-6986-F-H**

Image Sensor	1/1.8" progressive scan CMOS
Min. illumination	0.002 lux@F2.2, AGC ON
Lens	5mm X 4,
Shutter time	1/25s ~ 1/100,000s
Angle adjustment	Pan: 180°, Tilt: 78.4° Pan: 0° ~ 360°, Tilt 45° ~ 90°
Day & night	IR Cut filter
Video compression	H.264 /H.265/ MJPEG
Bit rate	32 Kbps ~ 16 Mbps
Max, image resolution	4096 × 1800
Frame rate	(4096 × 1800) 25/30fps
Network storage	NAS, ANR
System compatibility	ONVIF, PSIA, CGI, ISAPI
Communication interface	1 RJ45 10M / 100M / 1000M Ethernet port and 1 RS-485 interface
WDR	DWDR
On-board storage	Built-in SD slot, up to 128 GB
Audio	1/1
Alarm	1/1
Operating conditions	30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	DC 12V, AC 24V +/- 10%, PoE (802.3af)
Power consumption	22W
Dimensions	Ø 7.67" x 6.26"
Weight	2850g (6.28 lbs)