

HACC - R802MK

Mifare 2" Card Reader

EYESONIC™



Supports RS-485 and Wiegand (W26/W34) protocols. The built-in 13.56 MHz Mifare card reading module meets the ISO 14443-A standard and reads Mifare ID cards.

KEY FEATURES

- LED Indicator Displays Reader Status
- Tamper-Resistant Alarm
- Supports Mifare Cards
- RS-485 and Wiegand (W26/W34) Protocols
- Dust-proof and water-proof design
- Keypad

MODEL

HACC - R802M

Processor	32-bit
Reading Range	≤1.97" (≤50 mm)
Card Type	Mifare cards
ID Settings	via DIP switch
Communication Protocols	RS-485/Wiegand (set via DIP switch)
Audio Alert	Beeper
Keypad	Keypad w/12 keys (0~9, *, #)
LED Indicator	Power indicator, status indicator
Working Temperature	-4° to 149° F (-20° to +65° C)
Working Humidity	10% to 90% (non-condensing)
Dimensions	4.53" × 1.73" × 0.87" (115 mm × 44 mm × 22 mm)
Tamper Alarm	Supported
Protection Level	IP65
Certifications	CE, FCC, UL 60950-1
Power Supply	12 VDC
Power Consumption	≤2 W
Installing Method	Wall mounting with screws, does not support gang box